



- Luminaire for installation on wall or on ceiling – surface mounted.
- Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Polycarbonate diffuser: opal, self-extinguishing.
- Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.
- Protection rating: IP65.
- In compliance with EN 60598-1 standards.
- Class of insulation: I.
- Installation: wiring through a rubber cable holder (5mm<Ø<10mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

EU Regulation 874/2012 - Illumination equipment energy classes

A**FLUORESCENT VERSION:**Class A
TC-SEL/2G7**D****HALOGEN VERSION:**Class D
QT32/E27

.1 White



.6 Grey



.3 Anthracite



.4 Black



.18 Deep Brown



Ceiling fitting



Wall fitting




The fitting is
equipped with
1 cable inputProtection against
impact.
IK 09 - 10,00 joule

Glow wire test: 850°C



Sam / All-light



520123 **D**
QT 32 60W E27






5214123 **A**
TC-SEL 2x9W 2G7
Electronic ballast





Sam / Half Louvre




520110 **D**
QT 32 60W E27





5214110 **A**
TC-SEL 2x9W 2G7
Electronic ballast





Sam / Horizontal Visor




520107 **D**
QT 32 60W E27





5214107 **A**
TC-SEL 2x9W 2G7
Electronic ballast



Sam / Vertical Visor



520137 **D**
QT 32 60W E27



5214137 **A**
TC-SEL 2x9W 2G7
Electronic ballast

