

SHOWER HEAD CLEANING AND MAINTENANCE

CLEANING SHOWER HEADS WITH DESCALING DISK (RUB-CLEAN MODEL)

Warnings:

- SHOWER HEADS WITH A DESCALING DISK ARE FITTED WITH AN "EASY-CLEAN" SYSTEM COMPOSED OF SILICONE JETS, WHICH EXPAND WITH HOT WATER, THEREBY DETACHING THE FIRST LAYER OF LIMESCALE. BY REGULARLY RUBBING YOUR HAND OVER THE JETS, THE LIMESCALE WILL COME AWAY EASILY.
- THE FLOW REGULATION DEVICE ON THE JUNCTION CONNECTION MUST NOT BE REMOVED (see image 1).
- AFTER EACH USE, TURN THE SHOWER HEAD SLIGHTLY TO MORE EASILY RELEASE ANY RETAINED WATER.
- WE RECOMMEND IMMERSING THE DISMANTLED SHOWER HEADS IN HOT WATER AND WHITE WINE VINEGAR ON A PERIODIC BASIS (ONCE A MONTH) FOR 24 HOURS IN A 1/1 DILUTION; RINSE AND DRY AFTERWARDS.
- IN AREAS WHERE WATER IS MORE CALCAREOUS, WE RECOMMEND INSTALLING A WATER SOFTENER ONTO THE SYSTEM TO ENSURE THE ARTICLES SUPPLIED FUNCTION CORRECTLY.

CLEANING TRADITIONAL SHOWER HEADS

Warnings:

- THE FLOW REGULATION DEVICE ON THE JUNCTION CONNECTION MUST NOT BE REMOVED (see image 1).
- AFTER EACH USE, TURN THE SHOWER HEAD SLIGHTLY TO MORE EASILY RELEASE ANY RETAINED WATER, AND CLEAN IT CAREFULLY.
- WE RECOMMEND IMMERSING THE DISMANTLED SHOWER HEADS IN HOT WATER AND WHITE WINE VINEGAR ON A PERIODIC BASIS (ONCE A MONTH) FOR 24 HOURS IN A 1/1 DILUTION. RINSE AND DRY AFTERWARDS.
- IN AREAS WHERE WATER IS MORE CALCAREOUS, WE RECOMMEND INSTALLING A WATER SOFTENER ONTO THE SYSTEM TO ENSURE THE ARTICLES SUPPLIED FUNCTION CORRECTLY.

CLEANING METAL PARTS

WATER CONTAINS CALCIUM, WHICH SETTLES ON THE SURFACE OF PRODUCTS AND FORMS UNPLEASANT MARKS. FOR ROUTINE CLEANING OF THE PRODUCT, IT IS SUFFICIENT TO USE A DAMP CLOTH WITH SOME SOAP. RINSE AND DRY AFTER EACH USE.

IT IS RECOMMENDED THAT ONLY SOAP-BASED DETERGENTS BE USED.

NEVER USE DETERGENTS OR DISINFECTANTS THAT ARE ABRASIVE OR CONTAIN ALCOHOL, HYDROCHLORIC ACID, PHOSPHORIC ACID, BLEACH, CHLORINE, ETC...

N.B. THE GUARANTEE DOES NOT COVER DAMAGES CAUSED BY IMPURITIES OR LIMESCALE DEPOSITS.

image 1

